

IN THE CLAIMS:

Listing of Claims:

1. (Previously Presented) A foam chemical dispenser device, comprising:

a dispenser housing, said dispenser housing having a body portion defining a mixing module reception area;

a mixing module positioner adjustably supported by said dispenser housing between a mixing module hold position and a mixing module access position;

a finger releasable locking device which, when in a locking mode, locks said mixing module positioner in the hold position and when in a release mode provides for positioner adjustment to said access position, wherein said body portion includes at least one chemical passageway with outlet positioned for chemical communication with a mixing module chemical port when the mixing module is received within said reception area.
2. (Original) The device of claim 1 wherein said finger releasable locking device is a toggle clamp.
3. (Original) The device of claim 2 wherein said toggle clamp comprises an over-the-center latch.
4. (Original) The device of claim 3 wherein said latch has an adjustable contact member.
5. (Original) The device of claim 4 wherein said adjustable contact member includes a threaded rod with elastomeric tip.
6. (Original) The device of claim 1 wherein said mixing module positioner includes a pivotable member.

7. (Original) The device of claim 6 wherein said pivotable member includes a cover plate which has a pivotable first end pivotably attached to said body portion and has a contact section spaced from the pivotable first end, said locking device extends into contact with said contact section when in the locking mode.

8. (Previously Presented) The device of claim 7 wherein said cover plate has an outer edge which forms a peripheral closure seal relative to said body portion, but for an open end region which receives an outlet end of the mixing module.

9. (Previously Presented) A foam chemical dispenser device, comprising:
a dispenser housing, said dispenser housing having a body portion defining a mixing module reception area;

a mixing module positioner adjustably supported by said dispenser housing between a mixing module hold position and a mixing module access position;

a finger releasable locking device which, when in a locking mode, locks said mixing module positioner in the hold position and when in a release mode provides for positioner adjustment to said access position, wherein said locking device is adjustable into different compression levels relative to a mixing module received within said reception area.

10. (Previously Presented) The device of claim 9 wherein said locking device includes an extension member that is positioned for contact with said positioner and is adjustable in position to vary force levels placed on said positioner.

11. (Original) The device of claim 10 wherein said extension member has an elastomeric tip.

12. (Original) The device of claim 10 wherein said extension member comprises a threaded section.

13. (Original) The device as recited in claim 1 further comprising retention means designed for engagement with a mixing module received in the reception area of said body portion.

14. (Previously Presented) A foam chemical dispenser device, comprising:

a dispenser housing, said dispenser housing having a body portion defining a mixing module reception area;

a mixing module positioner adjustably supported by said dispenser housing between a mixing module hold position and a mixing module access position;

a finger releasable locking device which, when in a locking mode, locks said mixing module positioner in the hold position and when in a release mode provides for positioner adjustment to said access position; retention means designed for engagement with a mixing module received in the reception area of said body portion; wherein said retention means includes a male/female interconnection element.

15. (Original) The device as recited in claim 14 wherein said male/female interconnection element includes a projection extending within said reception area that is dimensioned for extension into a recess formed in the mixing module.

16. (Canceled)

17. (Previously Presented) The device as recited in claim 1 further comprising a solvent passageway with outlet positioned for solvent communication with a solvent port in the mixing module when the mixing module is received within said reception area.

18. (Presently Presented) A foam chemical dispenser device, comprising:

a dispenser housing, said dispenser housing having a body portion defining a mixing module reception area;

a mixing module positioner adjustably supported by said dispenser housing between a mixing module hold position and a mixing module access position;

a finger releasable locking device which, when in a locking mode, locks said mixing module positioner in the hold position and when in a release mode provides for positioner adjustment to said access position, a mixing module received within said reception area, said mixing module having one or more chemical ports having seal reception regions extending about said one or more chemical ports, and seals positioned within said seal reception regions which are configured to hold said seal in position relative to said mixing module, and said seals being placed in compressive contact with said main body when said positioner is in said hold position.

19. (Original) The device in claim 1 wherein said locking device is configured for one finger releasing and locking.

20. (Currently Amended) A foam chemical flow dispenser, comprising:

a foam chemical foam dispenser body with a mixing module placement portion;

a pivotable door pivotably supported by said dispenser body and comprising a covering plate, and said pivotable door being movable between a mixing module hold position and a mixing module access position; and

means for releasably locking said door in the hold position, wherein said means for releasably locking includes an over-the-center latch, and wherein said means for releasably

locking includes means for adjusting a compressive force imposed by said means for releasably locking on said pivotable door.

21. (Original) The dispenser of claim 20 wherein said means for releasably locking includes a toggle clamp.

22. (Canceled)

23. (Canceled)

24. (Currently Amended) A foam chemical flow dispenser, comprising:

a foam chemical foam dispenser body with a mixing module placement portion;
a pivotable door pivotably supported by said dispenser body and comprising a covering plate,
and said pivotable door being movable between a mixing module hold position and a mixing
module access position; and

means for releasably locking said door in the hold position, and ~~The dispenser of claim 20~~

wherein said door includes two hinge extension areas and an aperture therebetween which forms an outlet aperture for release of chemical by said mixing module.

25. (Currently Amended) A foam chemical flow dispenser, comprising:

a foam chemical foam dispenser body with a mixing module placement portion;
a pivotable door pivotably supported by said dispenser body and comprising a covering plate,
and said pivotable door being movable between a mixing module hold position and a mixing
module access position; and

means for releasably locking said door in the hold position, and ~~The dispenser of claim~~

~~20~~ wherein said dispenser further comprises a male/female positioning means for precision positioning of the mixing module relative to said placement portion.

26. (Currently Amended) The dispenser of claim [[20]] 25 wherein said male/female positioning means includes a projection extending out from said dispenser body and a reception cavity formed in said mixing module.

27. (Canceled)

28. (Previously Presented) A foam chemical dispenser, comprising:

a dispenser housing having a mixing module reception area;

a closure device supported by said dispenser housing;

said closure device being positionable relative to said dispenser housing to hold in position a mixing module received in the mixing module reception area of said dispenser; and

a latch having a first part which contacts said closure device to maintain said closure device in a mixing module hold position, and wherein said dispenser housing has a pair of chemical passageways leading to chemical outlets at the mixing module reception area, and said closure device is designed for contact with a mixing module received in said mixing module reception area to compress seals placed in a sealing relationship relative to the chemical outlets.

29. (Original) The dispenser as recited in claim 28 wherein said closure device is a door pivotably supported by said dispenser housing.

30. (Original) The dispenser as recited in claim 29 wherein said door has a pair of pivot legs pivotably attached to said dispenser housing and defining a mixing module dispensing outlet access port between said legs.

31. (Original) The dispenser as recited in claim 28 wherein said latch is a finger release latch.

32. (Canceled)

33. (Original) The dispenser as recited in claim 28 wherein said latch is an over-the-center toggle latch.

34. (Original) The dispenser as recited in claim 28 wherein said dispenser housing includes a main body and an upper cap section supported by said main body, and said latch has a first section secured to said upper cap and a closure device contact extension positioned for contact with said closure device.

35. (Original) The dispenser as recited in claim 34 said contact extension is adjustable to vary compression levels induced by said closure device on a mixing module received in said mixing module reception area.

36. (Canceled)

37. (Canceled)

38. (Canceled)

39. (Canceled)

40. (Canceled)

41. (Canceled)

42. (Canceled)

43. (Canceled)

44. (Canceled)

45. (Canceled)

46. (Canceled)